

SAFETY DATA SHEET



Date Prepared: 7.1.2015
MSDS No.: TruePrep
Revision Date: 5.18.2023
Revision No.: 5

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT DESCRIPTION: TruePrep (All Colors)

USE OR APPLICATION: Stump Die Spacer for use in dental laboratories

Company Information:

USA

International

Company Name: Harvest Dental Products, LLC
Street: 905 Columbia St.
City/ Zip: Brea, 92821
State/ Province: California
Country: USA
Telephone: 1+714-674-7400
Emergency Telephone: Infotrac: 1+800-535-5053

Harvest HPdent GmbH
Erwin-Dietrich-Straße 5
78244 Gottmadingen
BW
Germany
+49 7731 38 11 044
Infotrac INTL: 1+352-323-3500 (Collect)

2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

| | |
|--------------------|---|
| Flam. Liq. 2;H225 | Highly Flammable liquid and vapor. |
| Skin Irrit. 3;H316 | Causes mild skin irritation. (Not adopted by US OSHA) |
| Eye Irrit. 2;H319 | Causes serious eye irritation. |
| STOT SE 3;H336 | May cause drowsiness or dizziness. |

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Danger

H225 Highly flammable liquid and vapor.
H316 Causes mild skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness and dizziness.

Prevention:

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.
P235 Keep cool.
P240 Ground / bond container and receiving equipment.
P241 Use explosion-proof electrical / ventilating / light / equipment.

SAFETY DATA SHEET



Date Prepared: 7.1.2015
MSDS No.: TruePrep
Revision Date: 5.18.2023
Revision No.: 5

- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust / fume / gas / mist / vapors / spray.
- P262 Do not get in eyes, on skin, or on clothing.
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves / eye protection / face protection.

Response:

- P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.
- P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.
- P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.
- P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.
- P331 Do NOT induce vomiting.
- P332+313 If skin irritation occurs: Get medical advice / attention.
- P337+313 If eye irritation persists: Get medical advice / attention.
- P340 Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

Storage:

- P403+233 Store in a well ventilated place. Keep container tightly closed.
- P405 Store locked up.

Disposal:

- P501 Dispose of contents / container in accordance with local / national regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

| Ingredient/Chemical Designations | Weight % | GHS Classification | Notes |
|--|----------|--|--------|
| Butanone CAS Number: 0000078-93-3 | 50 - 74 | Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336 | [1][2] |
| Titanium dioxide CAS Number: 0013463-67-7 | 10 - 25 | Not Classified | [1][2] |
| Propylene glycol monomethyl ether acetate CAS Number: 0000108-65-6 | 1.0 - 10 | Flam. Liq. 3;H226 | [1] |
| Solvent naphtha (petroleum), light aromatic CAS Number: 0064742-95-6 | 1.0 - 10 | Asp. Tox. 1;H304 | [1] |
| Solvent naphtha (petroleum), light aliphatic CAS Number: 0064742-89-8 | 1.0 - 10 | Asp. Tox. 1;H304 | [1] |

SAFETY DATA SHEET



Date Prepared: 7.1.2015
MSDS No.: TruePrep
Revision Date: 5.18.2023
Revision No.: 5

| | | | |
|--|----------|---|--------|
| Carbon black CAS Number: 0001333-86-4 | 1.0 - 10 | Not Classified | [1][2] |
| Benzene, trimethyl- CAS Number: 0025551-13-7 | 1.0 - 10 | Flam. Liq. 2;H225 Acute Tox. 4;H302 Acute Tox. 4;H312 Skin Irrit. 2;H315 | [1] |
| 1,2,4-trimethylbenzene CAS Number: 0000095-63-6 | 1.0 - 10 | Flam. Liq. 3;H226 Acute Tox. 4;H332 Eye Irrit. 2;H319 STOT SE 3;H335 Skin Irrit. 2;H315 Aquatic Chronic 2;H411 | [1][2] |

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. FIRST AID MEASURES

4.1. Description of first aid measures

General

In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.

Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eyes

Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

Skin

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

Ingestion

Seek medical attention. If victim is drowsy/unconscious, place on the left side with head down. Do not give anything by mouth. If victim is conscious/alert, give no more than 2 glasses of water and induce vomiting (30 cc or 2 tbsp syrup of ipecac or stick finger in person's throat). Reduce above by half for child. Keep victim's head below hips.

4.2. Most important symptoms and effects, both acute and delayed

Overview

Inhalation/Ingestion: Solvent vapor or mist can cause headache, nausea, dizziness, incoordination, stupor, irritation of nose, throat, and lungs. Irritation of digestive tract. Nervous system depression (fatigue, drowsiness, dizziness)

Skin/Eyes: Burning, tearing, redness and swelling of eyes, transient corneal injury, drying and cracking of skin.

Carcinogenicity: None, but Proposition 65 (CA)-Warning- This product contains trace amounts of heavy metals which the State of Calif. has determined are carcinogens or cause reproductive toxicity. (As, Cd, Pb, Hg, and/or Ni are present in trace PPM.) **POTENTIAL HEALTH EFFECTS**

Eye Contact: May cause tearing, stinging, redness, irritation, and burns.

Inhalation: Irritating to respiratory tract. Prolonged or repeated breathing of very high vapor concentrations cause euphoria, excitation, and dizziness, headaches, nausea, and vomiting, abdominal pain, fatigue, muscular weakness. Aspiration into the lungs can cause CNS (central nervous system) and subsequent aspiration into the lungs can cause pulmonary edema and chemical

SAFETY DATA SHEET



Date Prepared: 7.1.2015
MSDS No.: TruePrep
Revision Date: 5.18.2023
Revision No.: 5

pneumonia depression. Chronic overexposure in high concentrations may produce CNS depression.

Ingestion: Irritation of the mouth, esophagus, and stomach can develop following ingestion.

Symptoms include burning of the mouth, sore throat, vomiting, nausea, dizziness, loss of consciousness. Due to its light viscosity, there is danger of aspiration into the lungs during vomiting. Aspiration can result in severe lung damage or death.

Skin Contact: Prolonged or repeated skin contact may cause moderate to severe irritation including itching and redness of the skin, defatting, and/or dermatitis. This product can also be absorbed through the skin and produce CNS symptoms. Single prolonged exposure is not likely to result in the product being absorbed through the skin in harmful amounts.

Signs And Symptoms Of Exposure: Eye irritation, respiratory irritation, drying and cracking of skin, dizziness, fatigue, headache, unconsciousness or asphyxiation. Chronic effects of ingestion and subsequent aspiration into the lungs can cause pneumatocele (lung cavity) formation and chronic lung dysfunction. Repeated breathing of vapors can cause effects to liver and kidneys.

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Inhalation

May cause drowsiness or dizziness.

Eyes

Causes serious eye irritation.

Skin

Causes mild skin irritation. (Not adopted by US OSHA)

5. FIRE FIGHTING MEASURE

5.1. Extinguishing media

Water spray, dry chemical, alcohol foam, carbon dioxide

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Oxides of Carbon

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Keep cool.

Ground / bond container and receiving equipment.

Use explosion-proof electrical / ventilating / light / equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust / fume / gas / mist / vapors / spray.

Do not get in eyes, on skin, or on clothing.

5.3. Advice for fire-fighters

Wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear. Use water spray to cool containers. For small bottle: Smother with water, wet blanket or towel.

SAFETY DATA SHEET



Date Prepared: 7.1.2015
MSDS No.: TruePrep
Revision Date: 5.18.2023
Revision No.: 5

Vapors can travel to a source of ignition and flash back. Material can form explosive vapors with air.

ERG Guide No. 128

6. ACCIDENTAL RELEASE MEASURES

- 6.1 **Personal precautions:** Store in cool, dry place.
- 6.2 **Environmental Precautions:** Avoid product spillage in sewage or drainage.
- 6.3 **Reclaiming Methods:** Wipe up with paper towels and dispose of in a suitable container.

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Ground all containers when transferring material. Periodically clean neck of bottle of resinous build up (clean inside of cap) to maintain proper seal. Do not smoke when using. Add thinner as needed, to keep proper thinness of material. See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Incompatible materials: Strong oxidizing agents, strong acids and strong bases.

Limit storage of flammable material to approved areas. Store bottles away from heat. Keep away from open flame of bunsen burner or furnace. Keep containers tightly sealed. Avoid storing near acids, chlorinated solvents. Storage Temp: Min: 4.4C/40F; Max: 49C / 120F; Cool Ambient Temperature preferred. Containers may be hazardous when empty. Emptied containers contain residue.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parameters

Exposure

| CAS No. | Ingredient | Source | Value |
|--------------|---|----------|--|
| 0000078-93-3 | Butanone | OSHA | TWA 200 ppm (590 mg/m ³) |
| | | ACGIH | TWA: 50 ppm STEL: 100 ppm |
| | | NIOSH | TWA 200 ppm (590 mg/m ³) ST 300 ppm (885 mg/m ³) |
| | | Supplier | No Established Limit |
| 0000095-63-6 | 1,2,4-trimethylbenzene | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | TWA 25 ppm (125 mg/m ³) |
| | | Supplier | No Established Limit |
| 0000108-65-6 | Propylene glycol monomethyl ether acetate | OSHA | No Established Limit |
| | | ACGIH | TWA: 50 ppm STEL: 75 ppm |

SAFETY DATA SHEET

Date Prepared: 7.1.2015
 MSDS No.: TruePrep
 Revision Date: 5.18.2023
 Revision No.: 5



| | | | |
|--------------|--|----------|--|
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| 0001333-86-4 | Carbon black | OSHA | TWA 3.5 mg/m ³ |
| | | ACGIH | TWA: 3 mg/m ³ 2B, Revised 2011, |
| | | NIOSH | TWA 3.5 mg/m ³ Ca TWA 0.1 mg PAHs/m ³ [in presence of polycyclic aromatic hydrocarbons (PAHs)] |
| | | Supplier | No Established Limit |
| 0013463-67-7 | Titanium dioxide | OSHA | TWA 15 mg/m ³ |
| | | ACGIH | TWA: 10 mg/m ³ 2B, Revised 2006, |
| | | NIOSH | Footnote ca |
| | | Supplier | No Established Limit |
| 0025551-13-7 | Benzene, trimethyl- | OSHA | No Established Limit |
| | | ACGIH | TWA: 5 ppm STEL: 15 ppm |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| 0064742-89-8 | Solvent naphtha (petroleum), light aliphatic | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| 0064742-95-6 | Solvent naphtha (petroleum), light aromatic | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |

Carcinogen Data

| CAS No. | Ingredient | Source | Value |
|--------------|---|--------|---|
| 0000078-93-3 | Butanone | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000095-63-6 | 1,2,4-trimethylbenzene | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000108-65-6 | Propylene glycol monomethyl ether acetate | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0001333-86-4 | Carbon black | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No; |
| 0013463-67-7 | Titanium dioxide | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No; |
| 0025551-13-7 | Benzene, trimethyl- | OSHA | Select Carcinogen: No |

SAFETY DATA SHEET

Date Prepared: 7.1.2015
 MSDS No.: TruePrep
 Revision Date: 5.18.2023
 Revision No.: 5



| | | | |
|--------------|--|------|--|
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0064742-89-8 | Solvent naphtha (petroleum), light aliphatic | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0064742-95-6 | Solvent naphtha (petroleum), light aromatic | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |

8.2. Exposure controls

| | |
|-----------------------------|---|
| Respiratory | If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators. |
| Eyes | Chemical-resistant goggles |
| Skin | Chemical-resistant gloves. (PVC or PE etc.) |
| Engineering Controls | Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn. |
| Other Work Practices | Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse. |

See section 2 for further details. - [Prevention]:

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|---|
| Appearance | White Liquid |
| Odor | Acetate |
| Odor threshold | Not determined |
| pH | Not Measured |
| Melting point / freezing point | -86 C/-123 F |
| Initial boiling point and boiling range | 80 C/176 F |
| Flash Point | -4 C/25 F (SFCC) |
| Evaporation rate (Ether = 1) | > 1 |
| Flammability (solid, gas) | Not Applicable |
| Upper/lower flammability or explosive limits | Lower Explosive Limit: 1 est. Upper Explosive Limit: 12 est. |
| Vapor pressure (Pa) | 20 C/68 F (at 70 mmHg) |

SAFETY DATA SHEET



Date Prepared: 7.1.2015
MSDS No.: TruePrep
Revision Date: 5.18.2023
Revision No.: 5

Vapor Density > 1 (Air = 1)
Specific Gravity Approx. 1
Solubility in Water Slight
Partition coefficient n-octanol/water (Log Kow) Not Measured
Auto-ignition temperature 516 C/961 F
Decomposition temperature Not Measured
Viscosity (cSt) Not Measured
Stable Vehicle and solvent - somewhat; Pigment - insoluble

9.2. Other information

No other relevant information.

10. STABILITY AND REACTIVITY

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid contact with ignition sources and keep containers away from incompatibles. Keep containers closed when not in use.

10.5. Incompatible materials

Strong oxidizing agents, strong acids and strong bases.

10.6. Hazardous decomposition products

Oxides of Carbon

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Based upon animal testing, the C9 aromatic hydrocarbon components (trimethylbenzenes and ethylmethylbenzenes) are presumed to cause fetal toxicity and/or decreased fetal and newborn weights if overexposure occurs during the early gestation period.

| Ingredient | Oral LD50, mg/kg | Skin LD50, mg/kg | Inhalation Vapor LC50, mg/L/4hr | Inhalation Dust/Mist LC50, mg/L/4hr | Inhalation Gas LC50, ppm |
|------------|---------------------|---------------------|---------------------------------------|---|--------------------------------|
|------------|---------------------|---------------------|---------------------------------------|---|--------------------------------|

SAFETY DATA SHEET

Date Prepared: 7.1.2015
 MSDS No.: TruePrep
 Revision Date: 5.18.2023
 Revision No.: 5



| | | | | | |
|---|----------------------------------|----------------------------------|-----------------------------|--------------------------|------------------------------|
| Butanone - (78-93-3) | 2,737.00, Rat - Category: 5 | 6,480.00, Rabbit - Category: NA | 32.00, Mouse - Category: NA | No data available | No data available |
| Titanium dioxide - (13463-67-7) | 10,000.00, Rat - Category: NA | 10,000.00, Rabbit - Category: NA | No data available | 6.82, Rat - Category: NA | No data available |
| Propylene glycol monomethyl ether acetate - (108-65-6) | 8,532.00, Rat - Category: NA | 5,000.00, Rabbit - Category: 5 | No data available | No data available | 4,345.00, Rat - Category: NA |
| Solvent naphtha (petroleum), light aromatic - (64742-95-6) | 6,800.00, Rat - Category: NA | 3,400.00, Rabbit - Category: 5 | No data available | No data available | No data available |
| Solvent naphtha (petroleum), light aliphatic - (64742-89-8) | > 5,000.00, Mouse - Category: NA | 3,000.00, Rabbit - Category: 5 | No data available | No data available | No data available |
| Carbon black - (1333-86-4) | 8,000.00, Rat - Category: NA | No data available | No data available | No data available | No data available |
| Benzene, trimethyl- - (25551-13-7) | No data available | No data available | No data available | No data available | No data available |
| 1,2,4-trimethylbenzene - (95-63-6) | 3,400.00, Rat - Category: 5 | 3,160.00, Rabbit - Category: 5 | 18.00, Rat - Category: 4 | No data available | No data available |

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

| Classification | Category | Hazard Description |
|-------------------------------|----------|---|
| Acute toxicity (oral) | --- | Not Applicable |
| Acute toxicity (dermal) | --- | Not Applicable |
| Acute toxicity (inhalation) | --- | Not Applicable |
| Skin corrosion/irritation | 3 | Causes mild skin irritation. (Not adopted by US OSHA) |
| Serious eye damage/irritation | 2 | Causes serious eye irritation. |
| Respiratory sensitization | --- | Not Applicable |
| Skin sensitization | --- | Not Applicable |
| Germ cell mutagenicity | --- | Not Applicable |
| Carcinogenicity | --- | Not Applicable |
| Reproductive toxicity | --- | Not Applicable |
| STOT-single exposure | 3 | May cause drowsiness or dizziness. |
| STOT-single exposure | --- | Not Applicable |
| STOT-repeated exposure | --- | Not Applicable |
| Aspiration hazard | --- | Not Applicable |

12. ECOLOGICAL INFORMATION

12.1. Toxicity

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and GHS and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See section 3 for details

SAFETY DATA SHEET

Date Prepared: 7.1.2015
 MSDS No.: TruePrep
 Revision Date: 5.18.2023
 Revision No.: 5



Aquatic Ecotoxicity

| Ingredient | 96 hr LC50 fish, mg/l | 48 hr EC50 crustacea, mg/l | ErC50 algae, mg/l |
|---|---------------------------------|----------------------------|---|
| Butanone - (78-93-3) | 400.00, Cyprinodon variegatus | 520.00, Daphnia magna | 500.00 (96 hr), Skeletonema costatum |
| Titanium dioxide - (13463-67-7) | 1,000.00, Fundulus heteroclitus | 5.50, Daphnia magna | 5.83 (72 hr), Pseudokirchneriella subcapitata |
| Propylene glycol monomethyl ether acetate - (108-65-6) | 100.00, Salmo gairdneri | 500.00, Daphnia magna | Not Available |
| Solvent naphtha (petroleum), light aromatic - (64742-95-6) | 9.22, Oncorhynchus mykiss | 6.14, Daphnia magna | 19.00 (72 hr), Selenastrum capricornutum |
| Solvent naphtha (petroleum), light aliphatic - (64742-89-8) | Not Available | Not Available | 4,700.00 (72 hr), Selenastrum capricornutum |
| Carbon black - (1333-86-4) | 1,000.00, Danio rerio | 5,600.00, Daphnia magna | 10,000.00 (72 hr), Scenedesmus subspicatus |
| Benzene, trimethyl- - (25551-13-7) | Not Available | 5.60, Palaemonetes pugio | Not Available |
| 1,2,4-trimethylbenzene - (95-63-6) | 7.72, Pimephales promelas | 3.60, Daphnia magna | Not Available |

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. TRANSPORT INFORMATION

| | DOT (Domestic Surface Transportation) | IMO / IMDG (Ocean Transportation) | ICAO/IATA |
|----------------------------------|---|--|--|
| 14.1. UN number | UN1993 | UN1993 | UN1993 |
| 14.2. UN proper shipping name | UN1993, Flammable liquids, n.o.s., (Methyl Ethyl Ketone), 3, II | Flammable liquids, n.o.s., (Methyl Ethyl Ketone) | Flammable liquids, n.o.s., (Methyl Ethyl Ketone) |
| 14.3. Transport hazard class(es) | DOT Hazard Class: 3 | IMDG: 3 Sub Class: Not Applicable | Air Class: 3 |
| 14.4. Packing group | II | II | II |
| 14.5. Environmental hazards | | | |
| IMDG | Marine Pollutant: No | | |

SAFETY DATA SHEET



Date Prepared: 7.1.2015
MSDS No.: TruePrep
Revision Date: 5.18.2023
Revision No.: 5

14.6. Special precautions for user

No further information

15. REGULATORY INFORMATION

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Toxic Substance Control Act (TSCA) All components of this material are either listed or exempt from listing on the TSCA Inventory.

WHMIS Classification B2 D2B

US EPA Tier II Hazards

Fire: Yes

Sudden Release of Pressure: No

Reactive: No

Immediate (Acute): Yes

Delayed (Chronic): No

EPCRA 311/312 Chemicals and RQs (lbs):

Butanone (5,000.00)

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

1,2,4-trimethylbenzene

Manganese oxide (Mn2O3)

Proposition 65 - Carcinogens (>0.0%):

Benzene, (1-methylethyl)-

Carbon black

TALC (Mg3H2(SiO3)4)

Titanium dioxide

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

New Jersey RTK Substances (>1%):

1,2,4-trimethylbenzene

Butanone

Carbon black

Titanium dioxide

Benzene, trimethyl-

SAFETY DATA SHEET



Date Prepared: 7.1.2015
MSDS No.: TruePrep
Revision Date: 5.18.2023
Revision No.: 5

Pennsylvania RTK Substances (>1%):

1,2,4-trimethylbenzene
Butanone
Carbon black
Titanium dioxide
Benzene, trimethyl-

16. OTHER INFORMATION

PREPARED BY: Sasha DerAvanessian

REVISION SUMMARY: This SDS replaces all prior MSDS.

HMIS RATING:

RATINGS:

0 = Minimal
2 = Slight
3 = Serious
4 = Severe

NFPA CODES



MANUFACTURER DISCLAIMER:

To the best of our knowledge, the information contained herein is accurate. However, Harvest Dental Products, LLC does not assume any liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.