

# SAFETY DATA SHEET

Date Prepared: 7.1.2015  
MSDS No.: SureFit  
Date Revised: 5.5.2021  
Revision No.: 3



## 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT DESCRIPTION:** SureFit (Gold/Silver/Thinner/MS1 Solvent)

**USE OR APPLICATION:** Die Spacer for use in dental laboratories

**Company Information:**

**USA**

**International**

Company Name:	Harvest Dental Products, LLC	Harvest HPdent GmbH
Street:	905 Columbia St	Erwin-Dietrich-Straße 5
City/ Zip:	Brea, 92821	78244 Gottmadingen
State/ Province:	California	BW
Country:	USA	Germany
Telephone:	1+714-674-7400	+49 7731 38 11 044
Emergency Telephone:	Infotrac: 1+800-535-5053	Infotrac INTL: 1+352-323-3500 (Collect)

## 2. HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

Flam. Liq. 2;H225	Highly Flammable liquid and vapor.
Skin Irrit. 3;H316	Causes mild skin irritation. (Not adopted by US OSHA)
Eye Irrit. 2;H319	Causes serious eye irritation.
Repr. 2;H361D	Suspected of damaging the unborn child.
STOT SE 3;H336	May cause drowsiness or dizziness.
Aquatic Acute 1;H400	Very toxic to aquatic life.
Aquatic Chronic 2;H411	Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



**Danger**

H225 Highly flammable liquid and vapor.  
H316 Causes mild skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness and dizziness.  
H361d Suspected of damaging the unborn child.

# SAFETY DATA SHEET



Date Prepared: 7.1.2015  
MSDS No.: SureFit  
Date Revised: 5.5.2021  
Revision No.: 3

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

## [Prevention]:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P235 Keep cool.

P240 Ground / bond container and receiving equipment.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

## [Response]:

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P308+313 IF exposed or concerned: Get medical advice / attention.

P332+313 If skin irritation occurs: Get medical advice / attention.

P337+313 If eye irritation persists: Get medical advice / attention.

P340 Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

P391 Collect spillage.

## [Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

## [Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

# SAFETY DATA SHEET



Date Prepared: 7.1.2015  
MSDS No.: SureFit  
Date Revised: 5.5.2021  
Revision No.: 3

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Butanone CAS Number: 0000078-93-3	50 - 75	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	[1][2]
Aluminum (Al) CAS Number: 0007429-90-5	10 - 25	Pyr. Sol. 1;H250 WaterReact. 2;H261	[1][2]
Copper CAS Number: 0007440-50-8	10 - 25	Not Classified	[1][2]
Zinc powder (stabilized) CAS Number: 0007440-66-6	1.0 - 10	Aquatic Acute 1;H400 Aquatic Chronic 1;H410	[1]
Toluene CAS Number: 0000108-88-3	0.10 - 1.0	Flam. Liq. 2;H225 Repr. 2;H361d Asp. Tox. 1;H304 STOT RE 2;H373 Skin Irrit. 2;H315 STOT SE 3;H336	[1][2]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

## 4. FIRST AID MEASURES

### 4.1. Description of first aid measures

<b>General</b>	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
<b>Inhalation</b>	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
<b>Eyes</b>	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
<b>Skin</b>	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
<b>Ingestion</b>	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

**Overview** INHALATION/INGESTION: Solvent vapor or mist can cause headache, nausea, dizziness, incoordination, stupor, irritation of nose, throat, lungs. Irritation of digestive tract. Nervous system depression (fatigue, drowsiness, dizziness)

SKIN/EYES: Burning, tearing, redness and swelling of eyes, transient corneal injury, drying and cracking of skin.

Medical Conditions - Generally Aggravated by Exposure: Copper/Zinc alloy powder - pre-existing skin disorders, respiration, liver, kidney & Wilson's disease.

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and

# SAFETY DATA SHEET



Date Prepared: 7.1.2015  
MSDS No.: SureFit  
Date Revised: 5.5.2021  
Revision No.: 3

respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

<b>Inhalation</b>	May cause drowsiness or dizziness.
<b>Eyes</b>	Causes serious eye irritation.
<b>Skin</b>	Causes mild skin irritation. (Not adopted by US OSHA)

## 5. FIRE FIGHTING MEASURE

### 5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO<sub>2</sub>, powder, water spray.  
Do not use: water jet.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Hydrogen Gas, CuO, ZnO  
Keep away from heat / sparks / open flames / hot surfaces - No smoking.  
Keep cool.  
Ground / bond container and receiving equipment.  
Use explosion-proof electrical / ventilating / light / equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid breathing dust / fume / gas / mist / vapors / spray.

### 5.3. Advice for fire-fighters

Special Fire Fighting Procedures: Wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH-approved or equivalent) and full protective gear. Use water spray to cool containers. Do not use water on open flame. Dike fire area gently with fine, dry sand to extinguish fire. Do not use halogenated hydrocarbon extinguishing agents.

Unusual Fire and Explosion Hazards: Vapors can travel to a source of ignition and flash back. Material can form explosive vapors with air. Avoid contact with water.

ERG Guide No. 128

## 6. ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

# SAFETY DATA SHEET



Date Prepared: 7.1.2015  
MSDS No.: SureFit  
Date Revised: 5.5.2021  
Revision No.: 3

## 6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

## 6.3. Methods and material for containment and cleaning up

Personal Precautions: Appropriate protective equipment must be worn for handling spill, see Section 8. If exposed to material, see Section 6.

Environmental Precautions: Warning - Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

Waste Disposal Method:

Spill Clean-up: Eliminate all ignition sources. Evacuate personnel to safe areas. Ventilate the area. Floor may be slippery, use caution. Soak up with inert absorbent material (Paper towel, sand, silica gel, sawdust). Avoid breathing vapor. Wear MSHA/NIOSH approved respirator. Note: Spills on porous surfaces can contaminate ground water. NORMAL DISPOSAL:

Waste Classification: Methyl Ethyl Ketone (78-93-3), 40 CFR 261.20-.24. For discard, this is classified as a hazardous waste with the characteristic of ignitability and toxicity. RCRA #D001. Reportable quantity is 100 lbs.(40 CFR 302) Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations. (See 40 CFR 268). For small quantity spills, allow solvent in paper towel to evaporate in well ventilated areas or outdoors (preferred).

CONTAMINATED PACKAGING: Empty containers should be taken for local recycling or waste disposal.

## 7. HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Store in accordance with the National Fire Protection Association's publication NFPA 30, Flammable and Combustible Liquids Code. 29 CFR 1910.106 applies to the handling, storage, and use of flammable and combustible liquids.

See section 2 for further details. - [Prevention]:

### 7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Incompatible materials: Water, acids, alkalis, chlorinated solvents

Precautions to Be Taken in Handling and Storing: Limit storage of flammable material to approved areas. Keep properly ventilated. Ground all containers when transferring material. Store bottles away from heat. Keep away from open flame of bunsen burner or furnace. Keep containers tightly sealed. Periodically clean neck of bottle of resinous build up (clean inside of cap) to maintain proper seal. Do not smoke when using. Avoid storing near acids, chlorinated solvents. Add thinner as needed, to keep proper thinness of material.

Other Precautions: Storage Temp: Min: 4.4C/40F; Max: 49C / 120F; Cool Ambient Temperature preferred. STEL: 125 ppm MEK. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Emptied containers contain residue. Follow all MSDS and labels. Keep away from spark.

See section 2 for further details. - [Storage]:

### 7.3. Specific end use(s)

No data available.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1. Control parameters

#### Exposure

CAS No.	Ingredient	Source	Value
0000078-93-3	Butanone	OSHA	TWA 200 ppm (590 mg/m3)
		ACGIH	TWA: 50 ppm STEL: 100 ppm

# SAFETY DATA SHEET



Date Prepared: 7.1.2015  
 MSDS No.: SureFit  
 Date Revised: 5.5.2021  
 Revision No.: 3

		NIOSH	TWA 200 ppm (590 mg/m <sup>3</sup> ) ST 300 ppm (885 mg/m <sup>3</sup> )
		Supplier	No Established Limit
0000108-88-3	Toluene	OSHA	TWA 200 ppm C 300 ppm 500 ppm (10-minute maximum peak)STEL 150 ppm
		ACGIH	TWA: 20 ppmR
		NIOSH	TWA 100 ppm (375 mg/m <sup>3</sup> ) ST 150 ppm (560 mg/m <sup>3</sup> )
		Supplier	No Established Limit
0007429-90-5	Aluminum (Al)	OSHA	TWA 15 mg/m <sup>3</sup> (total) TWA 5 mg/m <sup>3</sup> (resp)
		ACGIH	TWA: 1.0 mg/m <sup>3</sup> Revised 2008,
		NIOSH	TWA 10 mg/m <sup>3</sup> (total) TWA 5 mg/m <sup>3</sup> (resp)
		Supplier	No Established Limit
0007440-50-8	Copper	OSHA	TWA 1 mg/m <sup>3</sup> [*Note: The PEL also applies to other copper compounds (as Cu) except copper fume.]
		ACGIH	TWA: 0.2 mg/m <sup>3</sup> (fume) 1 mg/m <sup>3</sup> (dusts and mists)
		NIOSH	TWA 1 mg/m <sup>3</sup> [*Note: The REL also applies to other copper compounds (as Cu) except Copper fume.]
		Supplier	No Established Limit
0007440-66-6	Zinc powder (stabilized)	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

## Carcinogen Data

CAS No.	Ingredient	Source	Value
0000078-93-3	Butanone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000108-88-3	Toluene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0007429-90-5	Aluminum (Al)	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0007440-50-8	Copper	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0007440-66-6	Zinc powder (stabilized)	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

# SAFETY DATA SHEET



Date Prepared: 7.1.2015  
MSDS No.: SureFit  
Date Revised: 5.5.2021  
Revision No.: 3

## 8.2. Exposure controls

<b>Respiratory</b>	If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.
<b>Eyes</b>	Chemical-resistant goggles
<b>Skin</b>	Use chemical-resistant apron or other impervious clothing, and rubber boots if necessary, to avoid contaminating regular clothing and shoes and to prevent skin contact. Chemical resistant gloves.
<b>Engineering Controls</b>	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
<b>Other Work Practices</b>	Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	Gold or Silver or White (thinner) Liquid
<b>Odor</b>	sweet/sharp odor
<b>Odor threshold</b>	Not determined
<b>pH</b>	Not Measured
<b>Melting point / freezing point</b>	-86 C/-123 F initial
<b>Initial boiling point and boiling range</b>	80 C/176 F initial
<b>Flash Point</b>	-4 C/25 F (SFCC)
<b>Evaporation rate (Ether = 1)</b>	> 1 (Butyl Acetate = 1)
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Upper/lower flammability or explosive limits</b>	<b>Lower Explosive Limit:</b> 1.8 est <b>Upper Explosive Limit:</b> 11.5 est
<b>Vapor pressure (Pa)</b>	70 mmHg est. 20 C/68 F
<b>Vapor Density</b>	> 1
<b>Specific Gravity</b>	0.95 (H2O = 1)
<b>Solubility in Water</b>	Slight
<b>Partition coefficient n-octanol/water (Log Kow)</b>	Not Measured
<b>Auto-ignition temperature</b>	516 C/961 F
<b>Decomposition temperature</b>	Not Measured
<b>Viscosity (cSt)</b>	400 cPs mac
<b>% Volatile</b>	> 65% (Min)

## 9.2. Other information

No other relevant information.

# SAFETY DATA SHEET



Date Prepared: 7.1.2015  
 MSDS No.: SureFit  
 Date Revised: 5.5.2021  
 Revision No.: 3

## 10. STABILITY AND REACTIVITY

### 10.1. Reactivity

Hazardous Polymerization will not occur.

### 10.2. Chemical stability

Stable under normal circumstances.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

Avoid contact with water, mineral acids, chlorinated solvents

### 10.5. Incompatible materials

Water, acids, alkalis, chlorinated solvents

### 10.6. Hazardous decomposition products

Hydrogen Gas, CuO, ZnO

## 11. TOXICOLOGICAL INFORMATION

### Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Copper dust and mists: Can cause irritation of eyes, mucous membranes, skin and respiratory tract.

Chronic overexposures: Can cause reduction in the number of red blood cells (anemia), skin abnormalities (pigmentation changes) and hair discoloration.

Copper fume: Can cause irritation of eyes, mucous membranes and respiratory tract.

Acute overexposures: Can cause nausea, fever, chills, shortness of breath and malaise (metal fume fever).

Wilson's disease may be affected by copper exposure.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Butanone - (78-93-3)	2,737.00, Rat - Category: 5	6,480.00, Rabbit - Category: NA	32.00, Mouse - Category: NA	No data available	No data available
Aluminum (Al) - (7429-90-5)	No data available	No data available	No data available	No data available	No data available
Copper - (7440-50-8)	2,500.00, Rat - Category: 5	>2,000.00, Rat - Category: 5	No data available	5.11, Rat - Category: NA	No data available
Zinc powder (stabilized) - (7440-66-6)	No data available	No data available	No data available	No data available	No data available

# SAFETY DATA SHEET



Date Prepared: 7.1.2015  
 MSDS No.: SureFit  
 Date Revised: 5.5.2021  
 Revision No.: 3

Toluene - (108-88-3)	636.00, Rat - Category: 4	8,400.00, Rabbit - Category: NA	No data available	No data available	No data available
----------------------	---------------------------	---------------------------------	-------------------	-------------------	-------------------

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	3	Causes mild skin irritation. (Not adopted by US OSHA)
Serious eye damage/irritation	2	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	2	Suspected of damaging the unborn child.
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

## 12. ECOLOGICAL INFORMATION

### 12.1. Toxicity

Very toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

No additional information provided for this product. See Section 3 for chemical specific data.

### Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Butanone - (78-93-3)	400.00, Cyprinodon variegatus	520.00, Daphnia magna	500.00 (96 hr), Skeletonema costatum
Aluminum (Al) - (7429-90-5)	Not Available	Not Available	Not Available
Copper - (7440-50-8)	0.0103, Pimephales promelas	0.0025, Daphnia magna	0.018 (72 hr), Pseudokirchneriella subcapitata
Zinc powder (stabilized) - (7440-66-6)	0.182, Oncorhynchus tshawytscha	0.068, Daphnia magna	0.106 (72 hr), Pseudokirchneriella subcapitata
Toluene - (108-88-3)	5.80, Oncorhynchus mykiss	19.60, Daphnia magna	Not Available

# SAFETY DATA SHEET



Date Prepared: 7.1.2015  
MSDS No.: SureFit  
Date Revised: 5.5.2021  
Revision No.: 3

## 12.2. Persistence and degradability

There is no data available on the preparation itself.

## 12.3. Bioaccumulative potential

Not Measured

## 12.4. Mobility in soil

No data available.

## 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

## 12.6. Other adverse effects

No data available.

## 13. DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

## 14. TRANSPORT INFORMATION

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	UN1993	UN1993	UN1993
14.2. UN proper shipping name	UN1993, Flammable liquids, n.o.s., (Ethyl Methyl Ketone), 3, II	Flammable liquids, n.o.s., (Ethyl Methyl Ketone)	Flammable liquids, n.o.s., (Ethyl Methyl Ketone)
14.3. Transport hazard class(es)	DOT Hazard Class: 3	IMDG: 3 Sub Class: Not Applicable	Air Class: 3
14.4. Packing group	II	II	II
14.5. Environmental hazards			
IMDG	Marine Pollutant: Yes ( Zinc powder (stabilized) )		
14.6. Special precautions for user	No further information		

## 15. REGULATORY INFORMATION

Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.		
Toxic Substance Control Act ( TSCA)	All components of this material are either listed or exempt from listing on the TSCA Inventory.		
WHMIS Classification	B2 D2A		
US EPA Tier II Hazards	Fire: Yes Sudden Release of Pressure: No Reactive: No		

# SAFETY DATA SHEET



Date Prepared: 7.1.2015  
MSDS No.: SureFit  
Date Revised: 5.5.2021  
Revision No.: 3

**Immediate (Acute):** Yes

**Delayed (Chronic):** No

## EPCRA 311/312 Chemicals and RQs (lbs):

Butanone ( 5,000.00)

Copper ( 5,000.00)

Zinc powder (stabilized) ( 1,000.00)

## EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

## EPCRA 313 Toxic Chemicals:

Aluminum (Al)

Copper

Zinc powder (stabilized)

## Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

## Proposition 65 - Developmental Toxins (>0.0%):

Toluene

## Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

## Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

## New Jersey RTK Substances (>1%):

Aluminum (Al)

Butanone

Copper

Zinc powder (stabilized)

## Pennsylvania RTK Substances (>1%):

Aluminum (Al)

Butanone

Copper

Zinc powder (stabilized)

## 16. OTHER INFORMATION

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

# SAFETY DATA SHEET



Date Prepared: 7.1.2015  
MSDS No.: SureFit  
Date Revised: 5.5.2021  
Revision No.: 3

- H250 Catches fire spontaneously if exposed to air.
- H261 In contact with water releases flammable gases.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness and dizziness.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

**PREPARED BY:** Sasha DerAvanessian

**REVISION SUMMARY:** This SDS replaces all prior MSDS.

HMIS RATING:

RATINGS:


0 = Minimal

2 = Slight

3 = Serious

4 = Severe

NFPA CODES



**MANUFACTURER DISCLAIMER:**

To the best of our knowledge, the information contained herein is accurate. However, Harvest Dental Products, LLC does not assume any liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.