

SAFETY DATA SHEET



Date Prepared: 7.1.2015
MSDS No.: SureFit
Date Revised : 05.05.2021
Revision No.: 4

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT DESCRIPTION: SureFit(Colored) **USE OR APPLICATION:** Die Spacer for use in dental laboratories

Company Information:

USA

International

Company Name:	Harvest Dental Products, LLC	Harvest HPdent GmbH
Street:	905 Columbia St.	Erwin-Dietrich-Straße 5
City/ Zip:	Brea, 92821	78244 Gottmadingen
State/ Province:	California	BW
Country:	USA	Germany
Telephone:	1+714-674-7400	+49 7731 38 11 044
Emergency Telephone:	Infotrac: 1+800-535-5053	Infotrac INTL: 1+352-323-3500 (Collect)

2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Flam. Liq. 2;H225	Highly Flammable liquid and vapor.
Skin Irrit. 3;H316	Causes mild skin irritation. (Not adopted by US OSHA)
Eye Irrit. 2;H319	Causes serious eye irritation.
STOT SE 3;H336	May cause drowsiness or dizziness.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Danger

H225 Highly flammable liquid and vapor.
H316 Causes mild skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness and dizziness.

[Prevention]:

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.
P235 Keep cool.

SAFETY DATA SHEET



Date Prepared: 7.1.2015
MSDS No.: SureFit
Date Revised : 05.05.2021
Revision No.: 4

- P240 Ground / bond container and receiving equipment.
- P241 Use explosion-proof electrical / ventilating / light / equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust / fume / gas / mist / vapors / spray.
- P262 Do not get in eyes, on skin, or on clothing.
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves / eye protection / face protection.

[Response]:

- P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.
- P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.
- P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.
- P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.
- P331 Do NOT induce vomiting.
- P332+313 If skin irritation occurs: Get medical advice / attention.
- P337+313 If eye irritation persists: Get medical advice / attention.
- P340 Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

[Storage]:

- P403+233 Store in a well ventilated place. Keep container tightly closed.
- P405 Store locked up.

[Disposal]:

- P501 Dispose of contents / container in accordance with local / national regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Butanone CAS Number: 0000078-93-3	50 - 74	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	[1][2]
Titanium dioxide CAS Number: 0013463-67-7	10 - 25	Not Classified	[1][2]
C.I. Pigment Blue 15 CAS Number: 0000147-14-8	1.0 - 10	Not Classified	[1]
C.I. Pigment Red 170 CAS Number: 0002786-76-7	1.0 - 10	No Classification	[1]

SAFETY DATA SHEET



Date Prepared: 7.1.2015
 MSDS No.: SureFit
 Date Revised : 10.10.2018
 Revision No.: 3

Pigment yellow 151 CAS Number: 0031837-42-0	1.0 - 10		[1]
Propylene glycol monomethyl ether acetate CAS Number: 0000108-65-6	1.0 - 10	Flam. Liq. 3;H226	[1]
Solvent naphtha (petroleum), light aromatic CAS Number: 0064742-95-6	1.0 - 10	Asp. Tox. 1;H304	[1]
Iron oxide CAS Number: 0001309-37-1	1.0 - 10	Not Classified	[1][2]
Benzene, trimethyl- CAS Number: 0025551-13-7	1.0 - 10	Flam. Liq. 2;H225 Acute Tox. 4;H302 Acute Tox. 4;H312 Skin Irrit. 2;H315	[1]
1,2,4-trimethylbenzene CAS Number: 0000095-63-6	1.0 - 10	Flam. Liq. 3;H226 Acute Tox. 4;H332 Eye Irrit. 2;H319 STOT SE 3;H335 Skin Irrit. 2;H315 Aquatic Chronic 2;H411	[1][2]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. FIRST AID MEASURES

4.1. Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	Seek medical attention. If victim is drowsy/unconscious, place on the left side with head down. Do not give anything by mouth. If victim is conscious/alert, give no more than 2 glasses of water and induce vomiting (30 cc or 2 tbsp. syrup of ipecac or stick finger in person's throat). Reduce above by half for child. Keep victim's head below hips.

4.2. Most important symptoms and effects, both acute and delayed

Overview
 Inhalation/Ingestion: Solvent vapor or mist can cause headache, nausea, dizziness, incoordination, stupor, irritation of nose, throat, and lungs. Irritation of digestive tract. Nervous system depression (fatigue, drowsiness, dizziness)

Skin/Eyes: Burning, tearing, redness and swelling of eyes, transient corneal injury, drying and cracking of skin.

Carcinogenicity: None, but Proposition 65 (CA)-Warning- This product contains trace amounts of heavy metals which the State of Calif. has determined are carcinogens or cause reproductive

SAFETY DATA SHEET



Date Prepared: 7.1.2015
MSDS No.: SureFit
Date Revised : 05.05.2021
Revision No.: 4

toxicity. (As, Cd, Pb, Hg, and/or Ni are present in trace PPM.) **POTENTIAL HEALTH EFFECTS**

Eye Contact: May cause tearing, stinging, redness, irritation, and burns.

Inhalation: Irritating to respiratory tract. Prolonged or repeated breathing of very high vapor concentrations cause euphoria, excitation, and dizziness, headaches, nausea, and vomiting, abdominal pain, fatigue, muscular weakness. Aspiration into the lungs can cause CNS (central nervous system) and subsequent aspiration into the lungs can cause pulmonary edema and chemical pneumonia depression. Chronic overexposure in high concentrations may produce CNS depression.

Ingestion: Irritation of the mouth, esophagus, and stomach can develop following ingestion. Symptoms include burning of the mouth, sore throat, vomiting, nausea, dizziness, loss of consciousness. Due to its light viscosity, there is danger of aspiration into the lungs during vomiting. Aspiration can result in severe lung damage or death.

Skin Contact: Prolonged or repeated skin contact may cause moderate to severe irritation including itching and redness of the skin, defatting, and/or dermatitis. This product can also be absorbed through the skin and produce CNS symptoms. Single prolonged exposure is not likely to result in the product being absorbed through the skin in harmful amounts.

Signs And Symptoms Of Exposure: Eye irritation, respiratory irritation, drying and cracking of skin, dizziness, fatigue, headache, unconsciousness or asphyxiation. Chronic effects of ingestion and subsequent aspiration into the lungs can cause pneumatocele (lung cavity) formation and chronic lung dysfunction. Repeated breathing of vapors can cause effects to liver and kidneys. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Inhalation	May cause drowsiness or dizziness.
Eyes	Causes serious eye irritation.
Skin	Causes mild skin irritation. (Not adopted by US OSHA)

5. FIRE FIGHTING MEASURE

5.1. Extinguishing media

Water spray, dry chemical, alcohol foam, carbon dioxide

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Oxides of Carbon

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Keep cool.

Ground / bond container and receiving equipment.

Use explosion-proof electrical / ventilating / light / equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust / fume / gas / mist / vapors / spray.

SAFETY DATA SHEET



Date Prepared: 7.1.2015
MSDS No.: SureFit
Date Revised : 05.05.2021
Revision No.: 4

Do not get in eyes, on skin, or on clothing.

5.3. Advice for fire-fighters

Wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear. Use water spray to cool containers. For small bottle: Smother with water, wet blanket or towel.

Vapors can travel to a source of ignition and flash back. Material can form explosive vapors with air.

ERG Guide No. 128

6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Spill Clean-up: Eliminate all ignition sources. Evacuate personnel to safe areas. Ventilate the area. Floor may be slippery, use caution. Soak up with inert absorbent material (Paper towel, sand, silica gel, sawdust). Avoid breathing vapor.

Normal disposal: Waste Classification: Methyl Ethyl Ketone (78-93-3), 40 CFR 261.20-.24. For discard, this is classified as a hazardous waste with the characteristic of ignitability and toxicity. RCRA #D001. Reportable quantity is 100 lbs. (40 CFR 302) Incinerate liquid and contaminated solids in accordance with local, state and federal regulations. (See 40 CFR 268). For small quantity spills, allow solvent in paper towel to evaporate in well ventilated areas or outdoors (preferred).

Contaminated Packaging: Empty containers should be taken for local recycling or waste disposal. Dumping of product in ground or sewer may be illegal.

Eliminate ignition sources. Soak up with non-combustible absorbent material. Remove absorbent material for proper disposal.

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Ground all containers when transferring material. Periodically clean neck of bottle of resinous build up (clean inside of cap) to maintain proper seal. Do not smoke when using. Add thinner as needed, to keep proper thinness of material.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Incompatible materials: Strong oxidizing agents, strong acids and strong bases.

Limit storage of flammable material to approved areas. Store bottles away from heat. Keep away from open flame of bunsen burner or furnace. Keep containers tightly sealed. Avoid storing near acids, chlorinated solvents.

Storage Temp: Min: 4.4C/40F; Max: 49C / 120F; Cool Ambient Temperature preferred. Containers may be hazardous when empty. Emptied containers contain residue.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

SAFETY DATA SHEET



Date Prepared: 7.1.2015
 MSDS No.: SureFit
 Date Revised : 05.05.2021
 Revision No.: 4

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000078-93-3	Butanone	OSHA	TWA 200 ppm (590 mg/m ³)
		ACGIH	TWA: 50 ppm STEL: 100 ppm
		NIOSH	TWA 200 ppm (590 mg/m ³) ST 300 ppm (885 mg/m ³)
		Supplier	No Established Limit
0000095-63-6	1,2,4-trimethylbenzene	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	TWA 25 ppm (125 mg/m ³)
		Supplier	No Established Limit
0000108-65-6	Propylene glycol monomethyl ether acetate	OSHA	No Established Limit
		ACGIH	TWA: 50 ppm STEL: 75 ppm
		NIOSH	No Established Limit
		Supplier	No Established Limit
0000147-14-8	C.I. Pigment Blue 15	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0001309-37-1	Iron oxide	OSHA	TWA 15 mg/m ³ (total) TWA 5 mg/m ³ (resp)
		ACGIH	TWA: 5 mg/m ³ (dust or fume) STEL 10 mg/m ³ (as fume)
		NIOSH	TWA 5 mg/m ³
		Supplier	No Established Limit
0002786-76-7	C.I. Pigment Red 170	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0013463-67-7	Titanium dioxide	OSHA	TWA 15 mg/m ³
		ACGIH	TWA: 10 mg/m ³ 2B, Revised 2006,
		NIOSH	Footnote ca
		Supplier	No Established Limit
0025551-13-7	Benzene, trimethyl-	OSHA	No Established Limit
		ACGIH	TWA: 5 ppm STEL: 15 ppm
		NIOSH	No Established Limit
		Supplier	No Established Limit
0031837-42-0	Pigment yellow 151	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0064742-95-6	Solvent naphtha (petroleum), light aromatic	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit

SAFETY DATA SHEET



Date Prepared: 7.1.2015
 MSDS No.: SureFit
 Date Revised : 05.05.2021
 Revision No.: 4

		Supplier	No Established Limit
--	--	----------	----------------------

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000078-93-3	Butanone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000095-63-6	1,2,4-trimethylbenzene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000108-65-6	Propylene glycol monomethyl ether acetate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000147-14-8	C.I. Pigment Blue 15	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0001309-37-1	Iron oxide	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0002786-76-7	C.I. Pigment Red 170	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0013463-67-7	Titanium dioxide	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0025551-13-7	Benzene, trimethyl-	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0031837-42-0	Pigment yellow 151	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-95-6	Solvent naphtha (petroleum), light aromatic	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory

If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

Eyes

Chemical-resistant goggles

Skin

Chemical-resistant gloves. (PVC or PE etc.)

SAFETY DATA SHEET



Date Prepared: 7.1.2015
MSDS No.: SureFit
Date Revised : 05.05.2021
Revision No.: 4

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Assorted colors (i.e. yellow, blue, red, thinner-clear) Liquid
Odor	Acetate
Odor threshold	Not determined
pH	Not Measured
Melting point / freezing point	-86 C/-123 F
Initial boiling point and boiling range	80 C/176 F
Flash Point	-4 C/25 F (SFCC)
Evaporation rate (Ether = 1)	> 1
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 1 est. Upper Explosive Limit: 12 est.
Vapor pressure (Pa)	20 C/68 F (at 70 mmHg)
Vapor Density	> 1
Specific Gravity	Approx. 1
Solubility in Water	Slight
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	516 C/961 F
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured
Stable	Vehicle and solvent: somewhat; Pigment: insoluble

9.2. Other information

No other relevant information.

10. STABILITY AND REACTIVITY

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid contact with ignition sources and keep containers away from incompatibles. Keep containers closed when not in use.

SAFETY DATA SHEET



Date Prepared: 7.1.2015
 MSDS No.: SureFit
 Date Revised : 05.05.2021
 Revision No.: 4

10.5. Incompatible materials

Strong oxidizing agents, strong acids and strong bases.

10.6. Hazardous decomposition products

Oxides of Carbon

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Based upon animal testing, the C9 aromatic hydrocarbon components (trimethylbenzenes and ethylmethylbenzenes) are presumed to cause fetal toxicity and/or decreased fetal and newborn weights if overexposure occurs during the early gestation period.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Butanone - (78-93-3)	2,737.00, Rat - Category: 5	6,480.00, Rabbit - Category: NA	32.00, Mouse - Category: NA	No data available	No data available
Titanium dioxide - (13463-67-7)	10,000.00, Rat - Category: NA	10,000.00, Rabbit - Category: NA	No data available	6.82, Rat - Category: NA	No data available
C.I. Pigment Blue 15 - (147-14-8)	2,000.00, Rat - Category: 4	No data available	No data available	No data available	No data available
C.I. Pigment Red 170 - (2786-76-7)	No data available	No data available	No data available	No data available	No data available
Pigment yellow 151 - (31837-42-0)	No data available	No data available	No data available	No data available	No data available
Propylene glycol monomethyl ether acetate - (108-65-6)	8,532.00, Rat - Category: NA	5,000.00, Rabbit - Category: 5	No data available	No data available	4,345.00, Rat - Category: NA
Solvent naphtha (petroleum), light aromatic - (64742-95-6)	6,800.00, Rat - Category: NA	3,400.00, Rabbit - Category: 5	No data available	No data available	No data available
Iron oxide - (1309-37-1)	10,000.00, Rat - Category: NA	No data available	No data available	No data available	No data available
Benzene, trimethyl- - (25551-13-7)	No data available	No data available	No data available	No data available	No data available
1,2,4-trimethylbenzene - (95-63-6)	3,400.00, Rat - Category: 5	3,160.00, Rabbit - Category: 5	18.00, Rat - Category: 4	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

SAFETY DATA SHEET



Date Prepared: 7.1.2015
 MSDS No.: SureFit
 Date Revised : 05.05.2021
 Revision No.: 4

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	3	Causes mild skin irritation. (Not adopted by US OSHA)
Serious eye damage/irritation	2	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

12. ECOLOGICAL INFORMATION

12.1. Toxicity

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and GHS and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See section 3 for details

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Butanone - (78-93-3)	400.00, Cyprinodon variegatus	520.00, Daphnia magna	500.00 (96 hr), Skeletonema costatum
Titanium dioxide - (13463-67-7)	1,000.00, Fundulus heteroclitus	5.50, Daphnia magna	5.83 (72 hr), Pseudokirchneriella subcapitata
C.I. Pigment Blue 15 - (147-14-8)	Not Available	Not Available	Not Available
C.I. Pigment Red 170 - (2786-76-7)	Not Available	Not Available	Not Available
Pigment yellow 151 - (31837-42-0)	Not Available	Not Available	Not Available
Propylene glycol monomethyl ether acetate - (108-65-6)	100.00, Salmo gairdneri	500.00, Daphnia magna	Not Available
Solvent naphtha (petroleum), light aromatic - (64742-95-6)	9.22, Oncorhynchus mykiss	6.14, Daphnia magna	19.00 (72 hr), Selenastrum capricornutum
Iron oxide - (1309-37-1)	Not Available	Not Available	Not Available
Benzene, trimethyl- - (25551-13-7)	Not Available	5.60, Palaemonetes pugio	Not Available
1,2,4-trimethylbenzene - (95-63-6)	7.72, Pimephales promelas	3.60, Daphnia magna	Not Available

SAFETY DATA SHEET



Date Prepared: 7.1.2015
MSDS No.: SureFit
Date Revised : 05.05.2021
Revision No.: 4

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. TRANSPORT INFORMATION

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	UN1993	UN1993	UN1993
14.2. UN proper shipping name	UN1993, Flammable liquids, n.o.s., (Methyl Ethyl Ketone), 3, II	Flammable liquids, n.o.s., (Methyl Ethyl Ketone)	Flammable liquids, n.o.s., (Methyl Ethyl Ketone)
14.3. Transport hazard class(es)	DOT Hazard Class: 3	IMDG: 3 Sub Class: Not Applicable	Air Class: 3
14.4. Packing group	II	II	II
14.5. Environmental hazards			
IMDG	Marine Pollutant: No		
14.6. Special precautions for user	No further information		

15. REGULATORY INFORMATION

Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.
Toxic Substance Control Act (TSCA)	All components of this material are either listed or exempt from listing on the TSCA Inventory.
WHMIS Classification	B2 D2B
US EPA Tier II Hazards	Fire: Yes Sudden Release of Pressure: No Reactive: No Immediate (Acute): Yes Delayed (Chronic): No
EPCRA 311/312 Chemicals and RQs (lbs):	

SAFETY DATA SHEET



Date Prepared: 7.1.2015
MSDS No.: SureFit
Date Revised : 05.05.2021
Revision No.: 4

Butanone (5,000.00)

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

1,2,4-trimethylbenzene

C.I. Pigment Blue 15

Manganese oxide (Mn2O3)

Proposition 65 - Carcinogens (>0.0%):

Benzene, (1-methylethyl)-

Carbon black

Titanium dioxide

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

New Jersey RTK Substances (>1%):

1,2,4-trimethylbenzene

Butanone

Iron oxide

Titanium dioxide

Benzene, trimethyl-

Pennsylvania RTK Substances (>1%):

1,2,4-trimethylbenzene

Butanone

Iron oxide

Titanium dioxide

Benzene, trimethyl-

16. OTHER INFORMATION

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H226 Flammable liquid and vapor.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

SAFETY DATA SHEET



Date Prepared: 7.1.2015
MSDS No.: SureFit
Date Revised : 05.05.2021
Revision No.: 4

- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness and dizziness.
- H411 Toxic to aquatic life with long lasting effects.

PREPARED BY: Sasha DerAvanessian

REVISION SUMMARY: This SDS replaces all prior MSDS.

HMIS RATING:

RATINGS:

- 0 = Minimal
- 2 = Slight
- 3 = Serious
- 4 = Severe

NFPA CODES



MANUFACTURER DISCLAIMER:

To the best of our knowledge, the information contained herein is accurate. However, Harvest Dental Products, LLC does not assume any liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.